

DESCRIPTION	Water-based, acrylic copolymer-based basecoat paint to be applied under Cyclorama Green Topcoat Paint to ensure reaching optimal luminance and chrominance of the topcoat paint by use of its extremely high concealing power and unique coloristic properties. It has excellent adhesion on various types of surfaces; wood, various metals, vinyl, concrete, plaster, old painted surfaces coated with water-based decorative primers/paints, silicone free paints and some other plastic materials.	
APPLICATION AREA	Video and film productions	
PRODUCT CODE	CL60011	
COLOR	Cyclorama Green	
APPLICATION INSTRUCTIONS	Before application, ensure that all surfaces to be painted are clean, dry and dust free. There is no need to apply a regular primer before Cyclorama Green Basecoat Paint application. Applying one or two coats of Cyclorama Green Basecoat Paint will be enough under the Cyclorama Green Topcoat Paint due to very high concealing power to ensure the maximum chroma of Cyclorama Green Topcoat Paint. Apply one-two coats by roller/brush allowing 2 hours between successive coats.	
COVERAGE	Approx. 322 sq ft/gal (7.9 m ² /lt), 75 microns dry film thickness	
DRYING	Approx. 1-3 hours, 75 microns dry film, depending on temperature, humidity, and air ventilation.	
VOC	< 60 gr/lt	
CLEANING	Clean the application equipment with water.	
SHELF LIFE	12 months in original, closed containers at 41 – 95°F (5 –35°C). Protect from frost and direct sunlight.	
CONTENTS		<u>CAS NO</u>
	Water	7737-18-5
	Acrylic Polymer	25067-01-0
	TiO ₂	13463-67-7
	Pigment Yellow	6486-23-3
	Pigment Green	1328-53-6
	Monoethylene Glycol	107-21-1
	Texanol	25265-77-4
HAZARD STATEMENTS	H317 – May cause allergic skin reaction	
WARNING	If you scrape, sand, or remove old paint you may release lead which may cause serious illness.	
PRECAUTIONARY STATEMENTS:		
P101	If medical advice is needed; have product container label in hand	

P102	Keep out of reach of children
P233	Keep container tightly closed
P260	Do not breathe dust/fume/gas/mist/vapors/spray
P262	Do not get in eyes, on skin or on clothing.
P263	Avoid contact during pregnancy and while nursing
P270	Do not eat, drink, or smoke when using this product.
P312	Call a poison center or a doctor / physician if you feel unwell.
P501	Dispose the contents and containers in accordance with all local, regional, national, or international regulations.

Treatments such as sanding, burning off etc. of dry paint films may generate hazardous dust and/or fumes.

Work in well ventilated areas. Use suitable protective equipment as necessary.


TDS and SDS are available on request.

LEAD AND MERCURY FREE.




DANGER: Contains TiO_2 , whose dust and spray may cause respiratory, skin and eye irritation when inhaled. May cause cancer.


Protect from direct sunlight




Protect from Frost $<0^\circ\text{C}$




Clean the surface



Add water if needed



Stir



$^\circ\text{C}$

Application Temperature:
41 – 95°F (5 – 35°C)